



Corrugated plastic protection tube made of PA6; highly flexible and liquid tight

**Applications**

- cable protection: cable protection conduit, cable protection tube, cable protection hose, electric installation, switch cabinets, switch cabinet installation, cable harnessing/ cable assembly

**Properties**

- IP 68 to EN/ IEC 60529
- highly flexible
- good resistance to oil, gasoline and chemicals

- good resistance to alkalis and acids
- good resistance to chemicals
- flame-retardant according to: UL94-HB
- conforms to RoHS guideline
- approved to FMVSS 302 (flame-retardant)

**Temperature Range**

- -40°C to +120°C
- short time to 150°C

**Design, Material**

NORDUC® corrugated tube, parallel corrugated; wall: high grade polyamide (PA)

**Delivery variants**

- further diameters and lengths available on request
- grey (standard), black (standard)

Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Weight kg/m	PU	Order No.
<b>black</b>						
8,5	8,4	11,7	15	0,024	50	134-3012-9050
10	9,9	13,0	20	0,025	50	134-3013-9050
13	12,7	15,8	35	0,037	50	134-3016-9050
17	16,6	21,2	45	0,055	50	134-3021-9050
23	23,2	28,3	55	0,090	50	134-3028-9050
29	29,0	34,5	65	0,125	25	134-3035-9025
37	36,0	42,4	90	0,172	25	134-3042-9025
50	47,7	54,0	100	0,225	25	134-3054-9025
<b>grey</b>						
8,5	8,4	11,7	15	0,024	50	134-3012-9150
10	9,9	13,0	20	0,025	50	134-3013-9150
13	12,7	15,8	35	0,037	50	134-3016-9150
17	16,6	21,2	45	0,055	50	134-3021-9150
23	23,2	28,3	55	0,090	50	134-3028-9150
29	29,0	34,5	65	0,125	25	134-3035-9125
37	36,0	42,4	90	0,172	25	134-3042-9125
50	47,7	54,0	100	0,225	25	134-3054-9125
<b>slotted, black</b>						
7,5	7,0	10,0	-	0,022	50	134-3010-9155
8,5	8,4	11,7	-	0,024	50	134-3012-9155
10	9,9	13,0	-	0,025	50	134-3013-9155
13	12,7	15,8	-	0,037	50	134-3016-9155
17	16,6	21,2	-	0,055	50	134-3021-9155
23	23,2	28,3	-	0,090	50	134-3028-9155
29	29,0	34,5	-	0,125	25	134-3035-9156
37	36,0	42,4	-	0,172	25	134-3042-9156

Further technical data on [www.norres.com](http://www.norres.com). The right to make technical modifications is reserved. All values have been determined at 20°C and are approx. values.



Nominal width connecting part	I.D. mm	O.D. mm	Bending Radius (middle of hose)	Weight kg/m	PU	Order No.
50	47,7	54,0	-	0,225	25	134-3054-9156
<b>two-part, black</b>						
8,5	6,2	11,2	70	0,031	50	134-3011-9151
10	7,9	12,9	75	0,040	50	134-3013-9151
13	10,3	15,8	100	0,070	50	134-3016-9151
17	13,9	21,0	120	0,093	50	134-3021-9151
23	20,5	28,3	170	0,140	50	134-3028-9151
29	26,6	34,5	180	0,185	25	134-3035-9152
37	32,0	41,8	200	0,275	25	134-3042-9152
50	43,0	54,2	240	0,320	25	134-3054-9152

## Accessories



NORDUC® A-GK65-A 183 M/P



GK 169 M/P