

## Acid, chemical & multipurpose

**ALFAGOMMA**

↔		↔		⌚	⌚	⌒		⌒	⌚	⌚
mm	inch	mm	inch	bar	psi	mm	inch	%	kg/m	lb/ft
25	1	37	1,46	10	150	100	4,00	90	0,940	0,630
40	1 1/2	52	2,05	10	150	140	5,50	90	1,100	0,740
50	2	62	2,44	10	150	150	6,00	90	1,450	0,970
63*	2 1/2	77	3,03	10	150	175	7,00	90	2,050	1,380
65	2 5/8	77	3,03	10	150	175	7,00	90	2,250	1,510
75*	3	89	3,50	10	150	250	10,00	90	2,400	1,610
80	3 1/8	93	3,66	10	150	250	10,00	90	3,100	2,080
100	4	121	4,76	10	150	350	14	90	4,4	2,95
NA	LA	NEU	EMEA	SA	AP	AU				

\* Pitch for UK market



### 5J551

**Acid-chemical S&D 10 bar (150 psi) - standard duty  
BS 5842**

**Inner wire:** Polypropylene coated steel wire

**Tube:** Polypropylene film

**Cover:** Grey PVC coated fabric with longitudinal white stripe

**Outer wire:** Galvanised steel wire

**Use:** Acid and chemical suction and delivery. Specially designed for tank truck applications

**Safety factor:** 4:1

**Temperature:** -30 °C +80 °C (-22 °F +176 °F)

**Electrical Conductivity:** Ensured by the 2 wires in contact with fittings