



### APPLICAZIONI

- Tubo per aspirazione o mandata di oli minerali con un contenuto aromatico fino al 20%.
- Non idoneo al trasporto di carburanti, benzina, gasolio, idrocarburi clorurati, idrocarburi aromatici, esteri e chetoni.

### COSTRUZIONE SOTTOSTRATO

- Gomma NBR, colore nero, liscio.

### RINFORZI

- Inserzioni tessili sintetiche, ad alta resistenza.
- Spirale in acciaio incorporata.
- Cavetto di rame inserito.

### COPERTURA

- Gomma base CR, colore nero, resistente all'abrasione, all'ozono, all'invecchiamento, ondulata, impronta tela.

### MARCATURA

- Logo MTG, "Made in Italy"
- Listino longitudinale giallo.



### FATTORE DI SICUREZZA

- ≥ 3 volte la pressione di esercizio.

### TEMPERATURA

- Da -20°C a +80°C.
- Punta a +100°C in funzione ai liquidi convogliati.

### APPLICATION

- Corrugated hose for suction and delivery duties suitable for mineral oils with an aromatic content up to max. 20%.
- Not suitable for transport of fuels, petrol, diesel fuel, chlorinated hydrocarbons, aromatic hydrocarbons, esters and ketones.

### COSTRUCTION TUBE

- NBR rubber, black, smooth.

### REINFORCEMENT

- High strenght plies of synthetic cord.
- Embedded steel helix wire.
- Built-in copper wire.

### COVER

- CR based rubber, black, corrugated, resistant to abrasion, ozone, ageing, cloth finish.

### MARKING

- MTG Logo, "Made in Italy".
- Yellow stripe.



### SAFETY FACTOR

- ≥ 3 times working pressure.

### TEMPERATURE RANGE

- From -20°C up to +80°C.
- Peaks at max +100°C depending on conveyed media.

### TOLLERANZE DIMENSIONALI / SIZE TOLERANCES:

Diametro interno / I.D. : ISO 1307 - Lunghezza / Length : ISO 1307

DIAMETRO INTERNO INTERNAL DIAMETER [mm]	RAGGIO DI CURVATURA BENDING RADIUS [mm]	PRESSIONE DI ESERCIZIO WORKING PRESSURE [bar]	VACUUM VACUUM [bar]	PESO TEORICO THEORETICAL WEIGHT [kg/m]	LUNGHEZZA MAX. LENGTH MAX. [m]
75	375	10	-0,8	2,80	40
80	400	10	-0,8	3,20	40
100	500	10	-0,8	4,20	40